


SHAFTS SCREENER
MB-HDS212



SPECIFICATIONS

	Recommended excavator	ton	5 - 10
	Recommended backhoe loader	ton	8 - 9*
	Recommended skid steer loader**	ton	3 - 4
	Weight	ton	0,48
	Load capacity	m³	0,15
	Pressure	bar	200 - 250
	Back pressure	bar	< 20
	Oil flow rate***	l/min	75 - 100
	Size A	mm	1220
	Size B	mm	815
	Size C	mm	710

* Only compatible with the posterior boom of a Backhoe.
** Please verify machine's Rated Operating Capacity.
*** The minimum hydraulic flow rate value must be alongside the required operating pressure.

SHAFT KIT

KIT	ADJUSTMENT*	APPLICATION
RQ8 Sifting kit	8 mm	Soil Aeration Sifting and sorting damp/dry materials
RQ20 Sifting kit	20 mm	
RQ50 Sifting kit	50 mm	
RM Mixer kit		Coal reduction Soil Aeration Compost Aeration Glass reduction Drywall reduction
RE8 Fine sifting kit	8.5 mm	Sifting damp/dry soil
RE16 Fine sifting kit	16 mm	
RC Compost kit	36.5 mm	Shredding foliage and small branches Composting

* Shafts in closed position.

OPTIONAL ACCESSORIES

Shaft holder	24 Month Warranty
RQ8 Sifting kit	RQ20 Sifting kit
RQ50 Sifting kit	RM Mixer kit
RE8 Fine sifting kit	RE16 Fine sifting kit
RC Compost kit	

APPLICATION AREAS

