

SHAFTS SCREENER MB-HDS320



SPECIFICATIONS



Recommended excavator

ton

18 - 24



Recommended loader*

ton

11 - 14

Weight

ton

2,10

Load capacity

m³

1,35

Pressure

bar

250 - 300

Back pressure

bar

< 20

Oil flow rate**

l/min

120 - 160

Size A

mm

2050

Size B

mm

1350

Size C

mm

1250

* Please verify machine's Rated Operating Capacity.


** The minimum hydraulic flow rate value must be alongside the required operating pressure.

SHAFT KIT

KIT

ADJUSTMENT*

APPLICATION



RQ8 Sifting kit

8 mm



RQ20 Sifting kit

20 mm

RQ50 Sifting kit

50 mm

Soil Aeration
Sifting and sorting damp/dry materials



RM Mixer kit

Coal reduction
Soil Aeration
Compost Aeration
Glass reduction
Drywall reduction



RE8 Fine sifting kit

8.5 mm

RE16 Fine sifting kit

16 mm

Sifting damp/dry soil



RC Compost kit

36.5 mm

Shredding foliage and small branches
Composting

* Shafts in closed position.

OPTIONAL ACCESSORIES

Shaft holder

24 Month Warranty

RQ8 Sifting kit

RQ20 Sifting kit

RQ50 Sifting kit

RM Mixer kit

RC Compost kit

RE8 Fine sifting kit

RE16 Fine sifting kit

APPLICATION AREAS



Demolitions and
Renovations



Road works and
Infrastructures



Enclosed Spaces



Urban Construction
Sites



Remote Areas and
Complex Logistics



Pipelines



Inert materials
recycling and Waste
management



Earthmoving and
Excavations



Environmental
Remediation



Agriculture and
Landscaping



Forest maintenance

